

Compact size TGG Based PM Optical Circulator- 980/1030/1040/1050/1064nm

Key Features

- Low Insertion Loss
- High Power Handling
- High Isolation
- PM and Non-PM are available
- Fiber can be customized
- High Reliability
- Excellent Temperature Stability

The TGG Based PM Optical Circulator is a high-performance light-wave component that routes incoming signals from Port 1 to Port 2, and incoming Port 2 signals to Port 3. They're characterized with low insertion loss, high isolation, high PER, high power handling, high return loss, excellent environmental stability and reliability. They are ideal for fiber laser and instrumentation applications.

If you do not see a standard circulator that meets your needs, we welcome the opportunity to review your desired specification and quote a custom circulator. Requests for custom fiber pigtailed, different wavelengths and handling power of operation or other specific needs will be readily addressed.

Applications

- Fiber optic Amplifiers
- Pump Laser Source
- Fiber optic Sensor
- Test and Measurement
- Instrumentation



For more Info

Please contact us at:

Tel: +86-755-23736280

Fax: +86-755-26746512


E-mail: sales@dkphotonics.com

<https://www.dkphotonics.com>

Add.:

4F, Bldg. 18, Qinghu Industrial Park,
Dahe Road, Longhua Dis.,
Shenzhen, China 518109

Package Dimension:



*Due to ongoing design improvements, the package size is subject to change. Please contact DK Photonics for confirmation if you have special requirements.



Compact size TGG Based PM Optical Circulator-980/1030/1040/1050/1064nm

Performance Specifications

Parameters	Unit	Values
Central Wavelength	nm	980/1030/1040/1050/1064
Operating Wavelength Range	nm	±10
Typ. Peak Isolation	dB	28
Min. Isolation, λ_c , 23 °C	dB	23
Typ. Insertion Loss, 23 °C	dB	0.8
Max. Insertion Loss, 23 °C	dB	1.2
Min. Extinction Ratio(fast axis blocked)	dB	20
Min. Cross Talk	dB	45 (Typ. 50)
Min. Return Loss	dB	45
Power Handling (total pass)	W	0.5,3,5,10
Max. Peak Power for ns Pulse	kW	10, 20 (for typical pulse application)
Max. Tensile Load	N	5
Fiber Type	-	PM980 fiber, PM1060L, PM10/125 SC, or other
Operating Temperature	°C	0 ~ + 70
Storage Temperature	°C	-40 ~ +85
Dimensions	mm	32x20x18

1. Above specification are for device without connector, and may change without notice.
2. IL is 0.3 dB higher and RL is 5 dB lower, ER is 2dB lower (PM type) for each connector added.
3. The pass optical power is 2 W only for connector added, higher power requires splicing fibers.
4. Type B: Both axis working, Type F: Fast axis blocked, the default is Type B if without request (Only for PM type)
5. If there is pulse application, please be sure to inform us of pulse energy and peak power.

Order information P/N: CTPMOC-B/F-①-②-③-④-⑤-⑥-⑦(B: Both axis working, F:Fast axis blocked)

When you inquire, please provide the correct P/N number according to our ordering information and attach the appropriate description would be better. If need any connector, we do not recommend choosing a 250 μ m bare fiber pigtail. For high power applications, we recommend direct splicing without connectors.

①	②	③	④	⑤	⑥	⑦
Port	Operating Wavelength	Power Handling	Fiber Type	Fiber Diameter	Fiber Length	Connector
3:3-port	30:1030nm 64:1064nm 80:1080nm XX: Others	L:<0.5W 1:1W 3:3W 5:5W 10:10W	P98: PM980 XX: fiber name	25:250 μ m bare fiber 90:900 μ m Loose Fiber XX: Others	05:0.5m 10:1.0m 15:1.5m XX: Others	00: None FP: FC/PC FA: FC/APC XX: Others

Part Number Example: CTPMOC-F-3-30-1-P98-25-10-00

Description: Compact size TGG Based 1030nm 3-port Polarization Maintaining Optical Circulator, fast axis working, 1W power handling, PM980 fiber, with bare fiber, 1.0m length fiber pigtails, no connectors.

Ordering Information for Custom Parts

If you need to customize other specifications, please provide detailed description for your requirement.